


24" X 24" X 2"
FRAME ONLY. SPECIFIED BY PRECISIONCELL, INC.
 24" X 24" X 2" FRAME ONLY. SPECIFIED BY PRECISIONCELL, INC.



95% PCELL II MODEL NUMBER	NOMINAL SIZE	ACTUAL SIZE		MEDIA AREA (SQ. FT.)	PRESSURE DROP AND AIRFLOW @ 500 FPM		
		"A"	"B"		2"	4"	CFM
89655, 0*2424	24 X 24 X *	23 3/8"	23 3/8"	53	1.2	0.75	2000
89655, 0*1224	24 X 12 X *	23 3/8"	11 3/8"	26	1.2	0.75	1250
89655, 0*2024	24 X 20 X *	23 3/8"	19 3/8"	44	1.2	0.75	1400
89655, 0*1824	24 X 18 X *	23 3/8"	17 3/8"	39	1.2	0.75	1500
89655, 0*2020	20 X 20 X *	19 3/8"	19 3/8"	40	1.2	0.75	1400
89655, 0*2025	25 X 20 X *	24 3/8"	19 3/8"	46	1.2	0.75	1750
89655, 0*1625	25 X 16 X *	24 3/8"	15 3/8"	29	1.2	0.75	1400
89655, 0*1620	20 X 16 X *	19 3/8"	15 3/8"	36	1.2	0.75	1100

EXAMPLE OF MODEL NO. : 89655, 022424

MODEL NO. 89655, QTY: _____

MODEL NO. 89655, QTY: _____

MODEL NO. 89655, QTY: _____

MODEL NO. 89655, QTY: _____

- NOTES:**
1. FILTER TO BE RATED AT 95% IN ACCORDANCE WITH ASHRAE STANDARD 52.1-92.
 2. FRAME-HIGH WET STRENGTH 28 POINT CLAY COATED BEVERAGE BOARD.
 3. MEDIA-WET LAID MICRO FIBERGLASS.
 4. ADHESIVE-WHITE GLUE UTILIZED TO ATTACH STRAPS TO MEDIA AND FRAME TO FRAME.
 5. CLASSIFIED BY UL AS TO FLAMMABILITY ONLY. CLASS 2

CUSTOMER _____

CUSTOMER ORDER NO. _____

FLANDERS ORDER NO. _____

TITLE: FLANDERS PRECISIONCELL II
90-95%

Flanders DRAWING NO. _____ REV. _____

FLANDERS PRECISIONAIRE PCELL II 95%